

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
27 January 2005 (27.01.2005)


PCT

(10) International Publication Number  
**WO 2005/009024 A2**

- (51) International Patent Classification<sup>7</sup>: **H04N**  
ON M5A 4P7 (CA). MALCOLM, Michael, A. [US/US]; P.O. Box 7667, Aspen, CO 81612 (US).
- (21) International Application Number: **PCT/US2004/022847**
- (22) International Filing Date: **14 July 2004 (14.07.2004)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
60/488,367 15 July 2003 (15.07.2003) US  
10/655,496 3 September 2003 (03.09.2003) US
- (71) Applicant (for all designated States except US): **KALEI-DESCAPE, INC.** [US/US]; 339 North Bernardo Avenue, Suite 100, Mountain View, CA 94043 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KESTELOOT, Lawrence** [US/US]; 690 Pennsylvania Ave. #217, San Francisco, CA 94107 (US). **RECHSTEINER, Paul** [CA/CA]; 109 Front Street E., Apartment 627, Toronto,
- (74) Agent: **SWERNOFSKY, Steven, A.**; Swernofsky Law Group\_PC, P.O. Box 390013, Mountain View, CA 94039-0013 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: MASKING FOR PRESENTING DIFFERING DISPLAY FORMATS FOR MEDIA STREAMS



(57) Abstract: The invention provides a method and system capable of displaying media streams in a variety of formats on a screen that is dynamically adjustable to conform to displaying the media format that is the object of the media stream. Specifically, the invention allows the viewable area of a display screen (143) to be dynamically resized using masks (161) and sidebars (163), thus the resulting viewable area is optimized for the media stream. A database (110) includes metadata (113) for media presentations. When a user (190) selects a presentation to view, a server (130) associated with the user (190) queries the database (110) for metadata (113) associated with the presentation. The metadata (113) includes aspect ratio and other information for the presentation and sends a response to the server (130) that includes the metadata (113). A portion of the metadata (113) returned to the server (130) is used by a mask controller (160) to appropriately format the display screen (143) on which the user (190) will view the presentation.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— without international search report and to be republished upon receipt of that report

**Declarations under Rule 4.17:**

— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for all designations

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

## STREAMS

## 5

10

## 15

## 1. Field of the Invention

20

## 2. *Related Art*

25

A first known problem is that there are distinct aspect ratios for media streams, such as 4 x 3 (1.33:1) and 16 x 9 (1.78:1), but the physical screen has only one size. Other common aspect ratios are 1.66:1, 1.85:1, 2.20:1, and 2.35:1; the last three are sometimes called widescreen format. (Some of these aspect ratios are due to use of television, others due to use of screens.)

When an image is for example in 1.85:1 and the screen is 1.33:1 there is a mismatch, and the usual solution is to not use a portion of the screen. When the screen is reflective (such as when a projector is used), this presents a problem because the physical screen is highly reflective, so the part outside the intended media stream displays as an iridescent grey, rather than an unseen black. This diminishes the viewing experience of the viewer.

A first known solution includes velvet masks that can be placed at the top and bottom of the screen to cover the portion that is not being used for display. A second known solution is to letterbox the presentation by adding dark bars at the top and bottom; however, letterboxing doesn't really provide a solution because a TV screen still shows some grayish image.

A second known problem is that it is generally not possible to tell from the media stream itself what the correct aspect ratio should be, thus even when applying the velvet masks solution, manual user adjustment and refinement is required and may not provide the optimal presentation of the media.

A third known problem is that the actual masking used with the media stream might be imperfect and require adjustment, such as at only the top, only the bottom, or both. This is due to some media mastering houses that make errors in transfers of some media from older formats or have to compromise based on an old format or damage to the master media copy. In such cases, an image may be shifted horizontally and/or vertically by a significant number of pixels. In this case velvet masks that have been placed for a first presentation in a first format may obscure part of an image of a second media presentation in the same first format. Manual adjustment is once again an option, but it is an imperfect solution to home theater systems as today's users expect excellence at the touch of a button.

A fourth known problem is that some media streams are permanently reformatted inside an aspect ratio using black bars. This causes the image to be displayed smaller on a display screen with a different aspect ratio. For example, a movie in a ratio of 1.85:1 may have been letterboxed with black bars such that the displayed image including the black bars is now in a ratio of 1.33:1. If a user has a 1.85:1 display screen the image portion of interest to the user is trapped in the black bars.

Accordingly, it would be advantageous to provide a technique for displaying differing formats for media streams that improves on those techniques known in the art.

### Summary of the Invention

The invention provides a method and system capable of displaying media streams in a variety of formats on a screen whose aspect ratio is dynamically adjustable to conform to displaying the media format that is the object of the media stream. Specifically, the invention allows the viewable area of a display screen to be dynamically resized using masks and sidebars, thus the resulting viewable area is optimized for the media stream.

In a first embodiment, a database includes metadata for media presentations (such as movies). When a user selects a presentation to view, a server associated with the user queries the database for metadata associated with the presentation selected by the user. The metadata includes aspect ratio and other information for the presentation and sends a response to the server that includes the metadata.

The portion of the metadata returned to the server is used by a mask controller to appropriately format the display screen on which the user will view the presentation. This includes horizontal and vertical adjustments to the size of the viewing area.

In a second embodiment of the invention, additional formatting information is included for controlling the size and placement of the display area. For example, a combination of horizontal and vertical offset may be included such that even though the presentation is in a ratio of 1.85:1, the image has been moved down 25 pixels. Additional

commands may allow for subtitle space and other anomalies and special feature requirements when viewing some presentations. Resizing of the viewing area can occur at anytime before, during, or after a presentation as required.

5                   In a third embodiment, additional information may be included in the metadata that controls other devices such as audio systems and lighting.

                  In a fourth embodiment, the user may notify the server and/or the database that the metadata provided is inaccurate. This notification can include the settings that the  
10   user has found to be optimal. This may also occur when the database did not initially contain associated metadata for the presentation to be viewed by the user, thus the user is able to provide metadata that may be used by others.

                  In a fifth embodiment, at least some portion of the database is included at the  
15   local server such that the local server is periodically updated. Metadata can be customized by the user to meet their personal taste.

                  In a sixth embodiment, auto-detection of mask placement is accomplished by analyzing the media stream to determine the aspect ratio of the media stream and/or the  
20   location of the boundary between the displayed portion of the media stream of interest to the user and the displayed portion of the video stream not of interest to the user or not displayed.

                  In a seventh embodiment, masking may be accomplished using non-physical masks in the form of "light masking." Light masking displays bars, similar to the black bars  
25   used to letterbox some media streams, but the bars used for light masking are specifically chosen from a set of colors known to provide relatively equal screen burn-in yet remain unobtrusive.

                  After reading this application, those skilled in the art would recognize that the  
30   invention provides an enabling technology by which substantial advance is made in the art of media streams and digital content representative thereof.

Accordingly, it would be advantageous to provide a technique for presenting differing display formats that is not subject to drawbacks of the known art.

5

### Brief Description of the Drawings

Figure 1 shows a block diagram of a system including masking for presenting differing display formats for media streams.

10

Figure 2 illustrates mask and sidebar placement and movement in a method including operation of a system including masking for presenting differing formats for media streams.

15

Figure 3 shows a process flow diagram of a method including operation of a system including masking for presenting differing formats for media streams.

### Detailed Description of the Preferred Embodiment

20

In the description herein, a preferred embodiment of the invention is described, including preferred process steps and data structures. Those skilled in the art would realize, after perusal of this application, that embodiments of the invention might be implemented using a variety of other techniques not specifically described, without undue experimentation or further invention, and that such other techniques would be within the scope and spirit of the invention.

25

#### *Definitions*

30

The general meaning of each of these following terms is intended to be illustrative and in no way limiting.

- The phrase “media stream” describes information intended for presentation in a sequence, such as motion pictures including a sequence of frames or fields, or such as

audio including a sequence of sounds. As used herein, the phrase “media stream” has a broader meaning than the standard meaning for “streaming media,” (of sound and pictures that are transmitted continuously using packets and that start to play before all of the content arrives). Rather, as described herein, there is no particular requirement that “media streams” must be delivered continuously. Also as described herein, media streams can refer to other information for presentation, such as for example animation or sound, as well as to still media, such as for example pictures or illustrations, and also to databases and other collections of information.

• The phrase “digital content” describes data in a digital format, intended to represent media streams or other information for presentation to an end viewer. “Digital content” is distinguished from packaging information, such as for example message header information. For the two phrases “digital content” and “media stream,” the former describes a selected encoding of the latter, while the latter describes a result of presenting any encoding thereof.

• DVD, or digital versatile disc, is a technology standard that stores data on optical discs. Like the CD (compact disc) that came before it, a DVD holds its information in a digital format as bits denoting ones and zeros on the surface of the disc.

• The phrase “digital media,” and the like, describes physical media capable of maintaining digital content in an accessible form. Digital media includes disk drives (including magnetic, optical, or magneto-optical disk drives), as well as any other physical media capable of maintaining information, such as digital content.

• The term “bookmark” describes a reference to a logical location selected within a media stream. In one embodiment, bookmarks are not necessarily pre-selected by the creator or distributor of that media stream, and are possibly dynamically selected by a recipient of digital content representing that media stream. In one embodiment, presentation devices are capable of starting or restarting presentation from a selected bookmark.



- The term “watchpoint” describes a reference to a logical state of a presentation device, such as for example a logical location selected within a media stream. In one embodiment, watchpoints are capable of associating one or more events therewith, and (preferably) those one or more events might be conditioned on some other data or state information. For one example, the user might designate a bookmark at the beginning of a selected film clip, a watchpoint with the end of that same film clip, and an event associated with the watchpoint, which event directs a presentation device to return to a presentation state it was at before presenting from the bookmark. In this example, the film clip effectively acts as a media element capable of being inserted into another, different, media stream, without involving any other digital content associated with the larger media stream that contains that film clip.
- The term “overscan” refers to the part of the video frame (at the edge) not shown by a projector or display. Typically the overscan area is between one percent (1%) and four percent (4%) of image width or height.

The scope and spirit of the invention is not limited to any of these definitions, or to specific examples mentioned therein, but is intended to include the most general concepts embodied by these and other terms.

### *System Elements*

Figure 1 shows a block diagram of a system including masking for presenting differing display formats for media streams.

A system 100 includes a database 110, a communication network 120, one or more local servers 130, one or more local players 140, a controller 150, a mask controller 160, and other devices 170.

The database 110 includes a set of digital media metadata 113. The digital content metadata 113 includes technically descriptive information concerning digital content 111 useable in a system 100 as further described herein. For example, but without limitation, digital content metadata 113 can include such information as; aspect ratio,

surround sound encoding, pixel offset, equalization sound enhancement, available languages, subtitle availability.

In a preferred embodiment, the database 110 is physically remote to a user 190. In the preferred embodiment, the database 110 is under the supervision of an administrator (not shown but understood by one skilled in the art). In an alternative embodiment, at least some portion of the database 110 is physically local to the user 190. In this embodiment, the database 110 may be included with the local servers 130 or local players 140, and the user 190 may exercise at least some control over the database 110.

Digital content 111 includes audio, video, and combinations thereof as used to present sound and images. For example, but without limitation, digital content 111 can include; movies and songs as might be present on digital media such as Compact Discs, DVDs, Digital Audio Tape, and electronic computer storage devices.

The communication network 120 includes at least a portion of a communication network, such as a LAN, a WAN, the Internet, an intranet, an extranet, a virtual private network, a virtual switched network, or some combination thereof. In a preferred embodiment, the communication network 120 includes a packet switched network such as the Internet, as well as (in addition to or instead of) the communication networks just noted, or any other set of communication networks that enable the elements described herein to perform the functions described herein.

A communication link 121 operates to couple the elements of the system 100 such that the elements can communicate between each other as further described herein.

The system 100 includes one or more local servers 130. Each local server 130 includes a processor, a main memory, and software for executing instructions (not shown, but understood by one skilled in the art). This software preferably includes communications and control software capable of operating the local server 130 consistent with the invention as further explained herein.

The system 100 includes one or more local players 140. Each local player 140 includes a device capable of delivering digital content 111 to a presentation device. For example, but without limitation, a local player 140 may include a DVD player, a digital media stream decoder, a laser disc player, or some combination thereof.

5

A projector 141 includes any device capable of rendering digital content 111 as humanly viewable media. A display screen 143 includes a surface disposed to display an image. Generally the display screen is flat, smooth, and rectangular; however, there is no requirement that any of these properties exist and the only required property of the display screen 143 is that it has some light reflective property.

10

Two display screens 143 are illustrated in figure 1. The display screen 143 illustrated immediately adjacent to the projector 141 depicts a mask 161 at the top and a mask 161 at the bottom of the display screen 143. The second display screen 143 illustrated depicts a sidebar 163 at each side of the display screen 143. In a preferred embodiment of the invention, both masks 161 and sidebars 163 are used simultaneously on a single display screen 143. In alternative embodiments, any combination of masks 161 and sidebars 163 may be used.

15

The display screen 143 in a system 100 may have practically any dimension. Preferably, the display screen is a rectangle. The unaltered size and horizontal to vertical ratio of the display screen 143 is based on the preference of the user 190 and any physical limitations of the environment that the display screen 143 is in. A first user 190 may prefer an unaltered display screen 143 in a ratio of 4:3 (broadcast television standard). A second user 190 may prefer an unaltered display screen 143 in a 1.78:1 ratio. Regardless of the native size of the display screen 143, the invention may be applied to accommodate viewing of practically any digital content 111.

20

25

The controller 150 includes some portion of a computing device capable of interpreting data and issuing commands to a mask controller 160 and other devices 170 responsive to presentation of digital content 111.

30

The mask controller 160 includes some portion of a computing device capable of interpreting instructions from the controller 150. The mask controller 160 sends commands to move each mask 161 and sidebar 163 to hide or reveal an area of the display screen 143. The mask 161 includes one or more moveable non-reflective surfaces as further  
5 described herein. The sidebar 163 includes one or more moveable non-reflective surfaces as further described herein.

Other devices 170 include associative presentation accessories. For example, but without limitation, other devices include; lights, fans, heating and cooling systems,  
10 sound systems and combinations thereof. Under the direction of the controller 150, any one of these other devices 170 may be controlled as an integral element of the system 100 as further described herein.

A user 190 includes a human being generally disposed to select and view  
15 digital content 111.

### *Method of Operation*

Figure 2 illustrates mask and sidebar placement and movement in a method  
20 including operation of a system including masking for presenting differing formats for media streams.

In a preferred embodiment, each display screen 143 includes two masks 161. The first mask 161 runs horizontally across a top portion of the display screen 143 and is  
25 capable of reducing the vertical size of the display screen 143 as it obscures successively more screen area starting at the top edge of the display screen 143. A second mask 161 runs horizontally across a bottom portion of the display screen 143 and is capable of reducing the vertical size of the display screen 143 as it obscures successively more screen area starting at the bottom edge of the display screen 143.

30 The mask 161 is preferably a non-reflective material (such as, black velvet). The mask 161 may be of a relatively rigid material that moves statically retaining its shape and size or it may be flexible such that it stretches or accords to different dimensions.

In a preferred embodiment, each display screen 143 includes two sidebars 163. The first sidebar 163 runs vertically across a left portion of the display screen 143 and is capable of reducing the horizontal size of the display screen 143 as it obscures successively more screen area starting at the left most vertical edge of the display screen 143. A second sidebar 163 runs vertically across a right portion of the display screen 143 and is capable of reducing the horizontal size of the display screen 143 as it obscures successively more screen area starting at the right most vertical edge of the display screen 143.

The sidebar 163 is preferably a non-reflective material (such as, black velvet). The sidebar 163 may be of a relatively rigid material that moves statically retaining its shape and size or it may be flexible such that it stretches or accords to different dimensions as would a curtain. In a preferred embodiment each sidebar 163 is lowered into place from an area above the screen and raised when not needed. In an alternative embodiment, each sidebar 163 is moved in from the side. A combination of the preferred and alternative embodiments may also be used.

Due to the fact that the masks 161 and sidebars 163 do not have to be a rigid and static material, only the leading edge of the mask 161 and/or sidebar 163 would have to move to reveal or obscure an area of the display screen 143. For example, but without limitation, a sidebar 163 that included a velvet curtain could fold and unfold to reveal or obscure an area of the display screen 143. In the preferred embodiment, resizing of the sidebars 163 may be accomplished before, during, or after the sidebars 163 are lowered into place.

Resizing of the display screen 143 may occur in conjunction with bookmarks or watchpoints as defined in the definitions section. The user 190 may, by inserting bookmarks and watchpoints, cause video streams of different aspect ratios to be displayed in rapid succession. In such cases, the digital content metadata 113 associated with subsequent media streams is prefetched and processed appropriately. The user 190 is given some control over the implementation. The user 190 may choose to have the resizing take place just prior to presentation of a new media stream so that all video is viewable (not obstructed by masks 161 and sidebars 163) when the new media stream starts or at some time

thereafter. An intelligent mode would compare the aspect ratios of the two media streams and move ahead of the transition of the two media streams only those masks 161 and sidebars 163 that would not interfere with viewing of the current media stream.

5                   For some media presentations, absolute masking may be desirable. The absolute position of each sidebar 163 and mask 161 is specified to the mask controller 160 rather than the aspect ratio of the media stream to be presented. When this is done, overscan must be taken into account. Overscan is the part of the frame (at the edge) that is not displayed by the projector 141 and display screen 143. If the system believes that the top  
10 11% of the frame is black, but the projector 141 clips off the top 3%, then the top mask 161 needs to be brought down less than 11%. The same is true for the sidebars 163. Overscan for the system 100 is calibrated manually using standard video test patterns.

                  Some mask controllers 160 specify a mask's 161 absolute position in "points"  
15 and others in units of time. For example, fully closing the masks 161 may take 10 seconds, or may be specified as 100 points. Fully opening the masks may take 0 seconds (from fully open), or be specified as 0 points. In an embodiment of the invention, the local server 130 can communicate to the mask controller 160 the position of the masks 161 in units that the mask controller 160 can understand natively, such as points, time, or other unit of absolute  
20 position. In a calibration step the client device 130 is given two or more absolute locations on the screen 143 (using an on-screen calibration utility), each paired with a value that the mask controller 160 can recognize. For each desired location of a mask 161, the client device 130 can linearly interpolate to generate a value that can be used directly. In a preferred embodiment, three points are calibrated and a quadratic curve is used. Other  
25 curves could be used, such as linear, cubic, or exponential. A different curve can be used for top, bottom, and each side mask 161, and potentially for any other scenario, such as when changing video modes of a projector 141.

                  In figure 2, the "DIRECTIONS OF MOVEMENT" labels indicate the  
30 preferred plane of movement for the masks 161 and sidebars 163. In a preferred embodiment, the leading edges of the masks 161 and sidebars 163 would be horizontal and perpendicular respectively to the display screen 143. In an alternative embodiment, digital

content metadata 113 could produce non-horizontally aligned masks 161 and non-vertically aligned sidebars 163 yielding a trapezoidal viewing area of the display screen 143.

5 Some digital content 111, such as movies, requires an aspect ratio that is not directly related to digital content 111. This occurs, for example, when a foreign film is offered with subtitles. Filmmakers have historically placed the subtitles over the moving images towards the bottom in an effort to make them less obtrusive but readable. With the popularity of widescreen presentations, it is common for filmmakers to place subtitles in the black bar area below the moving images. This allows for easier reading of the text and the  
10 text does not obscure or interfere with the moving picture portion.

A problem associated with placing the subtitles in the black bar portion is that if masks 161 and sidebars 163 are placed at the boundaries of the moving picture portion of the digital content 111, the subtitles that are contained in the black bar portion are projected  
15 onto the lower mask 161 and not the display screen 143 making them hard or impossible to read. The invention ensures that digital content metadata 113 for every presentation and permutation thereof is available so that masks 161 and sidebars 163 are positioned correctly to allow for subtitles and other idiosyncrasies (for example, icons, ticker symbols, picture in picture portions and combinations thereof).

20

In an embodiment of the invention, resizing of the digital image and the viewable area of the display screen 143 may be desirable. For example, filmmakers often letterbox a widescreen presentation of a movie by adding black bars at the top and bottom of the movie essentially reformatting the media stream into another aspect ratio, such as 1.33:1  
25 (also known as standard 4:3 television).

In such a case it could be desirable to expand the visual image such that the portion the user 190 is interested in viewing is as large as possible. It will not matter if the black bars are projected on an area outside of the display screen 143 or on a mask 161 or  
30 sidebar 163 as the user does not wish to see them anyway. Digital content metadata 113 for positioning the masks 161 and sidebars 163 for media streams formatted in this manner is available in the database 110. The user can determine prior to viewing any digital content 111 whether they want the media stream optimized in this manner or not.

The system provides an onscreen display (OSD) to assist the user 190 in using the system. Whenever the user 190 executes a function, the OSD is activated to display helpful and needed information to the user 190. Generally, it is important that the OSD not interfere with the video presentation. Since the masks 161 and sidebars 163 will usually be at the edge of the video presentation, it is important for the system to take appropriate action to accommodate any OSD. Positional information for the masks 161 and sidebars 163 is maintained and used to calculate new positions for the masks 161 and sidebars 163, thus they can be temporarily moved to accommodate an OSD when it is important that the video presentation not be obscured in any way.

A debugging mode for setting up the system 100 utilizes the OSD for providing guidance to a technician. The OSD debugging mode displays positioning information for the masks 161 and sidebars 163. In a preferred embodiment, the OSD generates a picture frame at a selected aspect ratio, and the technician manually moves the masks 161 and sidebars 163 into place so as to meet the edges of the picture frame. This creates a calibration for the system including a set of values that is stored and ensures that all subsequent video presentations will have masks 161 and sidebars 163 at the optimum positions for a calibrated aspect ratio.

In an embodiment of the invention, auto-detection of mask placement is accomplished. This includes analyzing the media stream to determine the aspect ratio of the media stream and/or the location of the boundary between the displayed portion of the media stream of interest to the user and the displayed portion of the video stream not of interest to the user or not displayed. If auto-detection is successful, digital content metadata 113 can be updated in the database 110, so that auto-detection will not thereafter be necessary. The system 100 may request input from the user 190 to confirm that auto-detection was accurate or to provide additional manual adjustment of masks 161 and sidebars 163.

In an embodiment of the invention, masking may be accomplished using non-physical masks in the form of "light-masking." Light-masking can provide nonphysical equivalents of masks 161 and sidebars 163. Preferably, colors are chosen that are the least intrusive to the viewing experience of the user yet provide equal burn-in when displayed in conjunction with a media stream.



Light-masking can be applied in conjunction with physical masking such that burn-in of the display is eliminated and the light-masked area is obscured by the physical masks 161 and sidebars 163. Thus, the user 190 benefits by protecting their display device from burn-in and is not distracted by the light-masking as the physical masks 161 and sidebars 163 are in place.

In alternative embodiments, the picture frame may be replaced with a test pattern or any full-framed image with crisply, contrasted edges.

Figure 3 shows a process flow diagram of a method including operation of a system including masking for presenting differing formats for media streams.

A method 300 includes a set of flow points and steps. Although described serially, these flow points and steps of the method 300 can be performed by separate elements in conjunction or in parallel, whether asynchronously or synchronously, in a pipelined manner, or otherwise. There is no particular requirement that the flow points or steps must be performed in the same order as described, except where explicitly so indicated.

At a flow point 310, the system 100 is ready to process a request from a user 190.

At a step 311, the user 190 makes a selection from available digital content 111 contained on the local servers 130. The user 190 preferably makes their selection by viewing a list on the display screen 143. Alternatively, the user 190 may make their selection at a local player 140 or local server 130.

At a step 313, the local server 130 sends a request 191 to query the database 110 for the digital content metadata 113 associated with the digital content 111 selected by the user 190. In an embodiment of the invention, the user 190 pays a fee for the information retrieved from the database 110. The local server 130 provides identification of the user 190, and the database 110 maintains a transaction history for the user 190 so they can be billed at regular intervals. DVD media are identified by their DVD hash values.

At a step 315, the database 110 locates the digital media metadata 113 associated with the digital content 111 and sends a response 193 back to the local servers 130 that includes the digital media metadata 113.

5           At a step 317, the local server 130 processes the response 193 by passing identified information to the controller 150. This may include parsing the response 193 into sub-messages for individual processing by elements of the system 100. For example, but without limitation, parsing may extract data to be used by the mask controller 160 and data to be used by the controller 150 to instruct the other devices 170.

10           At a step 319, the controller identifies the portions of the response 193 that relate to the mask controller 160.

15           At a step 321, the mask controller 160 interprets the information it has received and issues commands to each mask 161 and sidebar 163 to move to a designated position per the response 193. These actions would preferably take place prior to the start of the presentation of the digital content 111 and would be updated during the presentation of the digital content 111 as designated in the response 193. Some directors have been known to start a movie in one aspect ratio and then move to another.

20           Currently, about six popular display ratios exist; however, it is within the scope and spirit of the invention to provide for yet unknown display ratios. As described herein, digital content metadata 113 provides the parameter values applied to mask 161 and sidebar 163 placements. Practically any vertical to horizontal ratio display screen 143 can be  
25           generated with the associated digital content metadata 113.

30           At a step 323, the controller 150 directs the other devices 170 consistent with the response 193. For example, but without limitation, the response could include the following instructions; 1) Dim house lights to 5%, 2) Set cooling fans to low/quiet speed, 3) Set surround system to 6.1 compliant, and 4) set DPS mode for audio system to rock concert preset. Some users 190 would have the other devices 170 and some would not. For those users 190 who do not have other devices 170 to control, any control messages for such would be ignored.

At a step 325, playback of the digital content 111 commences.

At a flow point 327, the system 100 has processed at least one request.

## 5 *Alternative Embodiments*

Although preferred embodiments are disclosed herein, many variations are possible which remain within the concept and scope of the invention. These variations would become clear to those skilled in the art after perusal of this application.

10

- The invention is not restricted to presentation of movies, but is also applicable to other media streams, such as for example animation, as well as to still media, such as for example pictures or illustrations, and to presentation of databases and other collections of information, or of user interfaces associated with operating systems or application software.

15

- The invention is not restricted to projection screens and physical masks, but is equally applicable to masking applications on other types of displays, such as for example plasma displays, where specifying the aspect ratio, frame size, and active video size can produce blanking of an inactive region of the display. This could be used to reduce screen burn-in.

20

An embodiment of the invention would use an electronic equivalent of a combination of masks 161 and sidebars 163. Placement of masks 161 and sidebars 163 would still be determined and implemented as in the preferred embodiment with the exception that instead of physical masks 161 and sidebars 163, electronic versions would be used (such as the previously mentioned display of a color that would reduce burn-in)

25

Those skilled in the art will recognize, after perusal of this application, that these alternative embodiments are illustrative and in no way limiting.

30

Claims

1. A method, including steps of adjusting an aspect ratio of a display in response to a remote database, the database including information associating aspect ratio information with media streams.

2. A method as in claim 1, wherein said aspect ratio is further adjusted in response to an on screen display, said on screen display indicating placement for some combination of masks and sidebars.

3. A method as in claim 1, including at least one of the steps of adjusting the aspect ratio in response to an input from a viewer; and sending that input to the database.

4. A method as in claim 1, wherein the information associating aspect ratio information includes at least one of:  
a preselected aspect ratio; and  
an adjustment from a known aspect ratio.

5. A method as in claim 1, wherein the steps of adjusting include automatically controlling one or more masks.

6. A method, including steps of  
presenting a media stream having a first aspect ratio R1 using a display screen  
having a second aspect ratio R2;  
receiving information from a source external to the media stream, that information relating to R1; and  
adjusting R2 in response to that information.

7. A method as in claim 6, wherein the steps of adjusting R2 include automatically moving masking.

8. A method as in claim 6, including steps of contracting the display

screen when the media stream includes a picture having a third aspect ratio  $R_3$ , with  $R_3 < R_1$ .

9. A method as in claim 6, including steps of expanding the display  
5 screen when the media stream includes a picture having a third aspect ratio  $R_3$ , with  $R_3 > R_1$ .

10. A method, including steps of  
recognizing a media stream with a first aspect ratio and user-interested  
10 viewable portion  $R$  embedded in a media stream having a second aspect ratio  $S$ , where  $S > R$ , whereby presentation of the media stream can be expanded to a relatively larger region of a display screen; and  
presenting the media stream in that relatively larger region.

11. A method as in claim 10, wherein a technique for embedding the first  
15 aspect ratio  $R$  includes letterboxing.

12. A method as in claim 10, wherein the first aspect ratio  $R$  is a known  
television standard.  
20

13. A method as in claim 10, wherein the second aspect ratio  $S$  is a known  
movie standard.

14. A method, including steps of  
25 recognizing an element to be presented with a media stream; and  
adjusting a target location for said element in response to an aspect ratio of that media stream.

15. A method as in claim 14, wherein those steps of adjusting include  
30 adjusting masking of the display screen in response to said element and the media stream; and  
positioning the element in an effective display region not blocked by masking.

16. A method as in claim 14, wherein said steps of adjusting include  
adjusting the aspect ratio in response to said element and the media stream;  
and

positioning the element in an effective display region not blocking any  
5 substantial portion of the media stream.

17. A method as in claim 14, wherein said steps of adjusting include  
positioning the target location in an effective display region not blocked by masking.

10 18. A method as in claim 14, wherein said steps of adjusting include  
positioning the target location in an effective display region not blocking any substantial  
portion of the media stream.

19. A method as in claim 14, wherein that element includes at least one  
15 of: a caption, a closed-caption, a subtitle, a translation, a ticker feed.

20. A method as in claim 1, wherein said steps of adjusting are responsive  
to a correlation between values in said database and DVD hash values.

20 21. A method, including steps of  
positioning some combination of masks and sidebars without regard for the  
aspect ratio of the media presentation, said positioning using absolute positional data values.

22. A method as in claim 21, wherein said positioning includes  
25 compensation for projector overscan.

23. A method for adjusting the aspect ratio of a display including steps of  
identifying a media stream to be presented;  
querying a database for metadata associated with said media stream;  
30 parsing said metadata, said parsing yielding one or more informational  
components;  
interpreting at least one of said informational components; and  
moving one or more display masks in response to said interpreting, said

display masks capable of obscuring and revealing some portion of said display.

24. A method of claim 23, wherein said display masks include one or more physical objects.

5

25. A method of claim 23, wherein said display mask includes an area of displayed light, said light of at least one hue determined to reduce screen burn-in at a transition boundary between an adjacently displayed image stream.

10

26. A method as in claim 23, wherein said identifying includes reading at least one DVD hash value, whereby a particular media stream is identified by computing said hash value as a part of said media stream and using said hash value as a key for said first database.

15

27. A method as in claim 23, wherein said identifying includes media streams at bookmarks.

28. A method as in claim 23, wherein said identifying includes media streams at watchpoints.

20

29. A method of claim 27, wherein said metadata includes some combination of: an aspect ratio, audio encoding specification, other device control information.

25

30. Apparatus including  
a database including information associating aspect ratio information with media streams;

memory or mass storage capable of receiving that information in response to one of those media streams; and

30

a masking controller capable of adjusting an aspect ratio of a display screen in response to information in that memory or mass storage.

31. The apparatus of claim 30, wherein said aspect ratio data is adjusted

by an input from a viewer.

32. The apparatus of claim 30, wherein the information associating aspect ratio information includes at least one of:

- 5           a pre-selected aspect ratio; and  
          an adjustment from a known aspect ratio.

33. The apparatus of claim 30, wherein said adjusting includes automatically controlling the position of one or more masks or sidebars.

10

34. A method of doing business, including steps of  
          providing access to information associating aspect ratio information with  
media streams; and  
          collecting a fee in response to those steps of providing access.

15

35. A method of claim 34, wherein said information associating aspect ratio information with media streams includes data for controlling some combination of a set of masks and a set of sidebars, said set of masks and set of sidebars adjusting the aspect ratio of the viewable portion of a display screen.

20

36. An information signal maintained in memory, mass storage, or on a communication path, the information signal including  
          a first media stream having a first aspect ratio R1, having been produced in  
response to a second media stream having a second aspect ratio R2, wherein

25

R1 > R2;  
          the first media stream is relatively larger than the second media stream; and  
          the first media stream does not include letterboxing.

37. A method, including adjusting the active area of a display in response  
30 to a remote first database, said first database including information associating some combination of aspect ratio information, horizontal size information, vertical size information, resolution, anamorphic compression, letterboxing with media streams.



38. A method as in claim 37, wherein said active area of said display is a reflective portion of said display visible to the human viewer.

39. A method as in claim 37, wherein said active area of said display is an illuminated portion of said display visible to a human viewer.

40. A method as in claim 37, wherein said active area may be further adjusted in response to an onscreen display, said on screen display indicating placement for some combination of masks and sidebars.

41. A method as in claim 37, wherein said information in said first database indicates a portion of a video frame occupied by a desired picture, wherein an active area of the display is adjusted to present the desired picture and exclude the remainder of the video frame.

42. A method as in claim 37, wherein said information in said first database indicates a portion of a video frame is occupied by a desired picture, whereby the active area of the display is adjusted by enlarging a projected image of said desired picture such that the active area contains the desired picture while excluding at least some portion of the video frame.

43. A method as in claim 42, wherein said information in said first database indicates that at least one video frame is letterboxed.

44. A method as in claim 37 including identifying a particular media stream by computing a hash of a part of the media stream and using said hash as a key with said first database.

45. A method as in claim 37, wherein said steps of adjusting are also responsive to logically local second database.

46. A method as in claim 45 wherein said second database includes information associating potentially active areas of said display with information in said first

database.

47. A method as in claim 45 wherein said second database includes information associating potentially active areas of said display with at least one media stream, said information originally obtained dynamically during playback of said at least one media stream.

48. A method as in claim 45, wherein said second database includes information related to projector overscan.

49. A method as in claim 46, wherein information in said second database may be further adjusted in response to an on screen display and input from a human viewer.

50. A method as in claim 49, wherein said on screen display indicates placement for some combination of masks and sidebars.

51. A method, including selecting a target location on a display for a first element of a video stream in response to a remote first database, said first database including information associating some combination of aspect ratio, horizontal size, vertical size, resolution, anamorphic compression, letterboxing with a second element of a media stream.

52. A method as in claim 51 including adjusting an active area of said display in response to said target location.

53. A method as in claim 52, wherein said active area is adjusted using some combination of masks and sidebars.

54. A method as in claim 52, wherein said first element is a motion picture and said second element includes some combination of a caption, a closed-caption, a subtitle, a translation, a ticker feed.

55. A method as in claim 37, wherein said steps of adjusting are responsive to a portion of the media stream being viewed.

56. A method as in claim 37, wherein said steps of adjusting are responsive to the triggering of one or more watchpoints.

57. A method for adjusting the aspect ratio of a display including steps of  
5 determining from a media stream to be presented the aspect ratio of said media stream;

calculating at least one informational component based on said determining;  
moving one or more display masks in response to said calculating, said display masks capable of obscuring and revealing some portion of said display.

58. Apparatus as in claim 30, wherein said database includes information associating some combination of at least one of aspect ratio information, horizontal size information, vertical size information, resolution, anamorphic compression, and letterboxing with at least one media stream.

59. The apparatus of claim 58, wherein said controller instructs movement of some combination of masks and sidebars, said masks and sidebars capable of adjusting the active area of a display screen.

60. A method of doing business as in claim 34, wherein the steps of providing access include providing access to a database, the database including at least some information associating some combination of at least one of aspect ratio information, horizontal size information, vertical size information, resolution, anamorphic compression, and letterboxing with at least one media stream.

61. A method as in claim 60, wherein said information includes data for controlling some combination of masks and sidebars, said masks and sidebars capable of adjusting the active area of a display screen.

62. A method as in claim 1, wherein said steps of adjusting include blanking an inactive area of said display with a color that minimizes burn-in when displayed.

63. A method, including steps of  
automatically determining the aspect ratio of a media stream; and  
adjusting an aspect ratio of a display in response to said step of automatically  
determining.

5

64. Apparatus, including  
means for adjusting an aspect ratio of a display in response to a remote  
database, the database including information associating aspect ratio information with media  
streams.

10

65. Apparatus as in claim 64, wherein said aspect ratio is further adjusted  
in response to an on screen display, said on screen display indicating placement for some  
combination of masks and sidebars.

15

66. Apparatus as in claim 64, including  
means for adjusting the aspect ratio in response to an input from a viewer; and  
means for sending that input to the database.

20

67. Apparatus as in claim 64, wherein the information associating aspect  
ratio information includes at least one of:  
a preselected aspect ratio; and  
an adjustment from a known aspect ratio.

25

68. Apparatus as in claim 64, wherein said means for adjusting includes  
automatically controlling one or more masks.

30

69. Apparatus, including  
means for presenting a media stream having a first aspect ratio R1 using a  
display screen having a second aspect ratio R2;  
means for receiving information from a source external to the media stream,  
that information relating to R1; and  
means for adjusting R2 in response to that information.

70. Apparatus as in claim 69, wherein said means for adjusting R2 includes automatically moving masking.

71. Apparatus as in claim 69, including means for contracting the display screen when the media stream includes a picture having a third aspect ratio R3, with  $R3 < R1$ .

72. Apparatus as in claim 69, including means for expanding the display screen when the media stream includes a picture having a third aspect ratio R3, with  $R3 > R1$ .

73. Apparatus, including  
means for recognizing a media stream with a first aspect ratio R and user-interested viewable portion embedded in that media stream having a aspect ratio S not equal to R, whereby presentation of the media stream can be expanded to a relatively larger region of a display screen; and  
means for presenting the media stream in that relatively larger region.

74. Apparatus as in claim 73, wherein means for embedding the user-interested viewable portion includes letterboxing.

75. Apparatus as in claim 73, wherein the first aspect ratio R includes a known television standard.

76. Apparatus as in claim 73, wherein the second aspect ratio S includes a known movie standard.

77. Apparatus, including  
means for recognizing an element to be presented with a media stream; and  
means for adjusting a target location for said element in response to an aspect ratio of that media stream.

78. Apparatus as in claim 77, wherein said means for adjusting includes means for adjusting masking of the display screen in response to said element and the media stream; and  
means for positioning the element in an effective display region not blocked  
5 by masking.

79. Apparatus as in claim 77, wherein said means for adjusting includes means for adjusting the aspect ratio in response to said element and the media stream; and  
10 means for positioning the element in an effective display region not overlapping any substantial portion of the media stream.

80. Apparatus as in claim 77, wherein said means for adjusting includes means for positioning the target location in an effective display region not blocked by  
15 masking.

81. Apparatus as in claim 77, wherein said means for adjusting includes means for positioning the target location in an effective display region not overlapping any substantial portion of the media stream.  
20

82. Apparatus as in claim 77, wherein that element includes at least one of: a caption, a closed-caption, a subtitle, a translation, a ticker feed.

83. Apparatus as in claim 64, wherein said means for adjusting is  
25 responsive to a correlation between values in said database and DVD hash values.

84. Apparatus, including  
means for positioning some combination of masks and sidebars without regard for the aspect ratio of the media presentation, said means for positioning using  
30 absolute positional data values.

85. Apparatus as in claim 84, wherein said means for positioning includes compensation for projector overscan.

86. Apparatus for adjusting the aspect ratio of a display including means for identifying a media stream to be presented; means for querying a database for metadata associated with said media stream;

5 means for parsing said metadata, said parsing yielding one or more informational components;

means for interpreting at least one of said informational components; and

means for moving one or more display masks in response to said interpreting, said display masks capable of obscuring and revealing some portion of said display.

10 87. Apparatus as in claim 86, wherein said means for identifying includes reading at least one DVD hash value, whereby a particular media stream is identified by computing said hash value as a part of said media stream and using said hash value as a key for said first database.

15 88. Apparatus as in claim 86, wherein said means for identifying includes media streams at bookmarks.

20 89. Apparatus as in claim 86, wherein said means for identifying includes media streams at watchpoints.

25 90. Apparatus of claim 86, wherein said metadata includes some combination of: an aspect ratio, audio encoding specification, other device control information.

30 91. Apparatus, including means for adjusting the active area of a display in response to a remote first database, said first database including information associating some combination of aspect ratio information, horizontal size information, vertical size information, resolution, anamorphic compression, letterboxing with media streams.

92. Apparatus as in claim 91, wherein said active area of said display is a reflective portion of said display visible to the human viewer.

93. Apparatus as in claim 91, wherein said active area of said display is an illuminated portion of said display visible to a human viewer.

94. Apparatus as in claim 91, wherein said active area may be further  
5 adjusted in response to an onscreen display, said on screen display indicating placement for some combination of masks and sidebars.

95. Apparatus as in claim 91, wherein said information in said first  
10 database indicates a portion of a video frame occupied by a desired picture, wherein an active area of the display is adjusted to present the desired picture and exclude the remainder of the video frame.

96. Apparatus as in claim 91, wherein said information in said first  
15 database indicates a portion of a video frame is occupied by a desired picture, whereby the active area of the display is adjusted by enlarging a projected image of said desired picture such that the active area contains the desired picture while excluding at least some portion of the video frame.

97. Apparatus as in claim 91, wherein said information in said first  
20 database indicates that at least one video frame is letterboxed.

98. Apparatus as in claim 91 including means for identifying a particular  
media stream by computing a hash of a part of the media stream and using said hash as a key  
with said first database.

25

99. Apparatus as in claim 91, wherein said means for adjusting are also  
responsive to a logically local second database.

100. Apparatus as in claim 99 wherein said second database includes  
30 information associating potentially active areas of said display with information in said first database.



101 Apparatus as in claim 99 wherein said second database includes information associating potentially active areas of said display with at least one media stream, said information originally obtained dynamically during playback of said at least one media stream.

5

102. Apparatus as in claim 99, wherein said second database includes information related to projector overscan.

103. Apparatus as in claim 99, wherein information in said second database  
10 may be further adjusted in response to an on screen display and input from a human viewer.

104. Apparatus as in claim 103, wherein said on screen display indicates placement for some combination of masks and sidebars.

15 105. Apparatus, including means for selecting a target location on a display for a first element of a video stream in response to a remote first database, said first database including information associating some combination of aspect ratio, horizontal size, vertical size, resolution, anamorphic compression, letterboxing with a second element of a media stream.

20

106. Apparatus as in claim 105 including means for adjusting an active area of said display in response to said target location.

107. Apparatus as in claim 106, wherein said active area is adjusted using  
25 some combination of masks and sidebars.

108. Apparatus as in claim 105, wherein said second element is a motion picture and said first element includes some combination of a caption, a closed-caption, a subtitle, a translation, a ticker feed.

30

109. Apparatus as in claim 91, wherein said means for adjusting are also responsive to at least a portion of the media stream being viewed.

110. Apparatus as in claim 91, wherein said means for adjusting are also responsive to triggering of one or more watchpoints.

111. Apparatus as in claim 64, said means for adjusting including means for blanking an inactive area of said display with a color that minimizes burn-in when displayed.

112. Apparatus, including means for automatically determining the aspect ratio of a media stream; and means for adjusting an aspect ratio of a display in response to said means for automatically determining.

113. An information signal maintained in memory, mass storage, or on a communication path, the information signal including a set of metadata associated with a media stream.

114. An information signal as in claim 113, wherein the metadata include instructions interpretable by a viewer device.

115. An information signal as in claim 114, wherein the viewer device includes at least one of a mask controller, one or more lights, one or more fans, one or more audio systems, one or more heating systems, one or more cooling systems.

116. An information signal as in claim 113, wherein the metadata is updateable.

117. An information signal as in claim 116, wherein the update is responsive to one or more user inputs.

118. An information signal as in claim 113, wherein the metadata is generated, at least in part, in response to the media stream.

119. An information signal as in claim 118, wherein the metadata includes at least one aspect ratio associated with the media stream.

120. An information signal as in claim 113, including  
5 a request identifying the media stream;  
wherein the metadata includes at least one aspect ratio associated with the media stream.

121. An information signal as in claim 113, including  
10 a response including at least some of the metadata;  
wherein the metadata includes at least one aspect ratio associated with the media stream.

122. An information signal maintained in a memory, mass storage, or on a  
15 communication path, the information signal including  
a set of displayable reference rectangles;  
the rectangles each predisposed to an aspect ratio; and  
the aspect ratio selectable by an operator.

123. An information signal maintained in a memory, mass storage, or on a  
20 communication path, the information signal including  
one or more mask values, having been produced in response to the manual positioning of one or more masks;  
one or more sidebar values, having been produced in response to the manual  
25 positioning of one or more sidebars; and  
a combination of said mask values and said sidebar values generating an aspect ratio.

124. Apparatus, including  
30 means for generating positional data for a set of masks and sidebars, said means for generating responsive to manual positioning of said set of masks and sidebars by an operator;  
means for calculating an aspect ratio from said positional data; and

means for storing said positional data in a database.

125. Apparatus, including

means for generating a request, said request indicating a media stream;

5

means for transmitting said request from a first server to a second server; and

means for identifying at least one media stream and at least one set of metadata associated with said request, said metadata including at least one set of aspect ratio information.

10

126. Apparatus of claim 125, including

means for generating a response in answer to said request, said response including at least one set of aspect ratio information;

15

means for transmitting said response from said second server to said first server;

means for parsing said response, said parsing extracting said at least one set of aspect ratio information from said response;

means for interpreting said aspect ratio information at a mask controller; and

means for moving a set of masks responsive to said interpreting.

20

127. Apparatus, including

means for analyzing a media stream, said analyzing generating positional data indicating a user-interested viewable portion and a user-uninterested viewable portion; and

25

means for placement of a set of masks responsive to said positional data, said placement obscuring said user-uninterested viewable portion.




FIG. 1

2/2




FIG. 2




FIG. 3